

Datasheet for: 116279


**Angled pivot fitting »value line« rotating, G 1/8 o. for hose Ø 6**

Angled pivot fitting »value line« rotating, G 1/8 o., for hose exterior Ø 6 mm, Operating pressure max 16 bar, nickel-plated brass. Low-priced yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Type number	56.018-6-E
Article number	116279
EAN/barcode	 4047322183918
Your price	3,33 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Collet	Stainless steel AISI 316
For tube O.D.	6 mm
L1	23.5 mm
L2	25.0 mm
Material	Nickel-plated brass
Max. operating temperature	70 °C
Min. operating temperature	-20 °C
O-ring	NBR, silicone-free
Operating pressure	max. 16 bar (at +20 °C)
Page No.	WEB
Page No. AS	AS111
Series	value line
Sleeve	Hostaform
Thread	G 1/8

## Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>Price</i>
116279	G 1/8	6 mm	3,33 € / Stk
116275	M5	4 mm	2,81 € / Stk
116278	G 1/8	4 mm	3,27 € / Stk
116280	G 1/8	8 mm	3,44 € / Stk
116276	G 1/4	6 mm	4,31 € / Stk
116277	G 1/4	8 mm	4,31 € / Stk

## More Pictures

