

Datasheet for: 110392


Push-in L-fitting, rotating, R 1/4 o., for hose exterior Ø 6 mm

Push-in L-fitting, rotating, R 1/4 o., for hose exterior Ø 6 mm, Working pressure max. 15 bar, Stainless steel 1.4404. For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	54.014-6 ES
Article number	110392
EAN/barcode	 4047322100090
Your price	44,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	6 mm
L1	21.5 mm
L2	24.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	ISO 7-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	R 1/4
Working pressure pulsate a/f	10.0 bar 14 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110392	R 1/4	6 mm	14 mm	44,91 € / Stk
110389	R 1/8	4 mm	10 mm	38,79 € / Stk
110390	R 1/8	6 mm	13 mm	37,66 € / Stk
110391	R 1/8	8 mm	13 mm	45,13 € / Stk
110393	R 1/4	8 mm	14 mm	48,31 € / Stk
110394	R 1/4	10 mm	16 mm	58,42 € / Stk
110395	R 3/8	10 mm	17 mm	68,30 € / Stk
110396	R 3/8	12 mm	22 mm	83,89 € / Stk
110397	R 1/2	12 mm	22 mm	74,88 € / Stk

More Pictures

