

Datasheet for: 110396


Push-in L-fitting, rotating, R 3/8 o., for hose exterior Ø 12 mm

Push-in L-fitting, rotating, R 3/8 o., for hose exterior Ø 12 mm, Working pressure max. 15 bar, Stainless steel 1.4404 . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	54.038-12 ES
-------------	--------------

Article number	110396
----------------	--------

EAN/barcode



4047322100236

Your price	83,89 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	12 mm
L1	28.0 mm
L2	30.5 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	ISO 7-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	R 3/8
Working pressure pulsate a/f	10.0 bar 22 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110396	R 3/8	12 mm	22 mm	83,89 € / Stk
110389	R 1/8	4 mm	10 mm	38,79 € / Stk
110390	R 1/8	6 mm	13 mm	37,66 € / Stk
110391	R 1/8	8 mm	13 mm	45,13 € / Stk
110392	R 1/4	6 mm	14 mm	44,91 € / Stk
110393	R 1/4	8 mm	14 mm	48,31 € / Stk
110394	R 1/4	10 mm	16 mm	58,42 € / Stk
110395	R 3/8	10 mm	17 mm	68,30 € / Stk
110397	R 1/2	12 mm	22 mm	74,88 € / Stk

More Pictures

