


Datasheet for: 110397


Push-in L-fitting, rotating, R 1/2 o., for hose exterior Ø 12 mm

Push-in L-fitting, rotating, R 1/2 o., for hose exterior Ø 12 mm, Working pressure max. 15 bar, Stainless steel 1.4404 . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

| | |
|----------------|--|
| Type number | 54.012-12 ES |
| Article number | 110397 |
| EAN/barcode |  4047322100007 |
| Your price | 74,88 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------------|------------------------|
| For tube O.D. | 12 mm |
| L1 | 28.0 mm |
| L2 | 33.5 mm |
| Material | Stainless steel 1.4404 |
| Max. medium temperature | 150 °C |
| Max. operating temperature | 150 °C |
| Max. working pressure | 15 bar |
| Min. medium temperature | -20 °C |
| Min. operating temperature | -20 °C |
| Page No. | WEB |
| Standard thread | ISO 7-1 |
| Suitable pipe materials | PVDF, PTFE, PA, PU |
| Thread | R 1/2 |
| Working pressure pulsate a/f | 10.0 bar 22 mm |

Variants

| Article number | Thread | For tube O.D. | a/f | Price |
|----------------|--------|---------------|-------|---------------|
| 110397 | R 1/2 | 12 mm | 22 mm | 74,88 € / Stk |
| 110389 | R 1/8 | 4 mm | 10 mm | 38,79 € / Stk |
| 110390 | R 1/8 | 6 mm | 13 mm | 37,66 € / Stk |
| 110391 | R 1/8 | 8 mm | 13 mm | 45,13 € / Stk |
| 110392 | R 1/4 | 6 mm | 14 mm | 44,91 € / Stk |
| 110393 | R 1/4 | 8 mm | 14 mm | 48,31 € / Stk |
| 110394 | R 1/4 | 10 mm | 16 mm | 58,42 € / Stk |
| 110395 | R 3/8 | 10 mm | 17 mm | 68,30 € / Stk |
| 110396 | R 3/8 | 12 mm | 22 mm | 83,89 € / Stk |

More Pictures

