


Datasheet for: 116374


Service unit 2-part »G«, PC container, 5 μ m, Size 300, G 3/8

Service unit 2-part »G«, PC container, Protective cage, 5 μ m, Size 300, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar . Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	GCL 12
Article number	116374
EAN/barcode	 4047322307581
Your price	82,28 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	115.0 mm
B	225.5 mm
Bowl	Polycarbonate container with protective cage
C	82.5 mm
Condensate drain	Semi-automatic
D	143.0 mm
Filter rating	5.0 μ m
Flow rate	1350 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. medium temperature	70 °C
Min. control range	1.5 bar
Page No.	WEB
Page No. AS	AS032
Sealant	NBR

Series
 Sight dome
 Size
 Spring bonnet
 Thread

G
 Brass/POM
 300
 POM
 G 3/8

Variants

Article number	Thread	Flow rate	Size	Condensate drain	Price
116374	G 3/8	1350 l/min	300	Semi-automatic	82,28 € / Stk
116375	G 3/8	1350 l/min	300	Fully-automatic	119,07 € / Stk
116377	G 1/2	1350 l/min	300	Fully-automatic	119,07 € / Stk
116372	G 1/4	1050 l/min	300	Semi-automatic	82,28 € / Stk
116376	G 1/2	1350 l/min	300	Semi-automatic	82,28 € / Stk
116380	G 1/2	3100 l/min	400	Semi-automatic	143,04 € / Stk
116378	G 3/8	3100 l/min	400	Semi-automatic	143,04 € / Stk
116373	G 1/4	1050 l/min	300	Fully-automatic	119,07 € / Stk
116379	G 3/8	3100 l/min	400	Fully-automatic	162,71 € / Stk
116381	G 1/2	3100 l/min	400	Fully-automatic	162,71 € / Stk

More Pictures

