


Datasheet for: 101530

Air-air-pressure amplifier (booster) without controller, G 3/8


Air-air-pressure amplifier (booster) without controller, G 3/8, Piston Ø 63 mm, Reinforced 2:1, Input pressure 2 - 10 bar . Pressure multipliers (boosters) allow a separate compressed air store with up to double pressure to be installed for selected devices in a compressed air system without an external energy source, i.e. it is possible to work with a maximum pressure of 20 bar in a standard 10 bar system (maximum ratio 2:1). This is achieved using a double piston, which is operated by a combination of integrated check valves in such a way that the booster works automatically until the target pressure is reached in a compressed air tank and is then automatically switched off. A tank is always required to build up the pressure and store the compressed air! Operation with filtered, unlubricated or lubricated compressed air possible (if lubrication is used, it must be continuous).

Type number	B-923
Article number	101530
EAN/barcode	 4047322284912
Your price	527,17 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

H	98.0 mm
Housing	Anodised aluminium
Jacket	Anodised aluminium jacket
L	290.0 mm
Max. input pressure	10 bar
Max. output pressure	20.0 bar
Max. temperature range	60 °C
Min. input pressure	2.0 bar
Min. temperature range	-10 °C
Mounting options	Any position, with 4 mounting holes
P2:P1	2:1
Page No.	HK179

Piston Ø 63 mm
 Sealant NBR
 Thread G 3/8

Variants

Article number	Piston Ø	Max. temperature range	Thread	Price
101530	63 mm	60 °C	G 3/8	527,17 € / Stk
101529	40 mm	50 °C	G 1/8	319,92 € / Stk

More Pictures

