


## Datasheet for: 141927

### Pushbutton safety coupling I.D. 6, ISO 6150 C, G 1/4 IT



Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, G 1/4 IT, Operating pressure max. 12 bar, Temp. -20 °C to 200 °C. High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling. After a second push the plug is released. This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded. The safety version meets ISO standard DIN EN ISO 4414. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

Type number	406.02-ES
Article number	141927
EAN/barcode	 4047322566872
Your price	17,87 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

Connection	G 1/4 IT
DN	6
Flow rate	1150 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 1$ bar
Housing	Stainless steel
Length	55.0 mm
Max. operating pressure	12 bar
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK577
Page No. SK	SK060
Plug profile	acc. ISO 6150 C
Pushbutton	Stainless steel
Sealant	FKM
Spring	Stainless steel
Threaded piece	Galvanised steel
Valve	Brass

a/f

20 mm

## Variants

Article number	Connection	Length	a/f	Price
141927	G 1/4 IT	55.0 mm	20 mm	17,87 € / Stk
141928	G 3/8 IT	55.0 mm	20 mm	18,89 € / Stk
141929	G 1/2 IT	58.0 mm	24 mm	18,89 € / Stk
141926	G 1/8 IT	53.0 mm	20 mm	20,68 € / Stk

## More Pictures

