


## Datasheet for: 141936

**Pushbutton safety coupling I.D. 6, ISO 6150 C, Sleeve I.D. 10**


Pushbutton safety coupling I.D.6, ISO 6150 C, Stainless steel, Sleeve I.D.10, Operating pressure max. 12 bar, Temp. -20°C to 200°C . High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling. After a second push the plug is released. This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded. The safety version meets ISO standard DIN EN ISO 4414. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

Type number	406.24-ES
Article number	141936
EAN/barcode	 4047322566926
Your price	18,89 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	I.D. 10
DN	6
Flow rate	1150 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 1$ bar
Housing	Stainless steel
Length	71.0 mm
Max. operating pressure	12 bar
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK577
Page No. SK	SK060
Plug profile	acc. ISO 6150 C
Pushbutton	Stainless steel
Sealant	FKM
Spring	Stainless steel
Threaded piece	Galvanised steel

Valve  
 a/f

 Brass  
 20 mm

**Variants**

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
141936	I.D. 10	18,89 € / Stk
141934	I.D. 6	31,27 € / Stk
141937	I.D. 13	31,27 € / Stk
141935	I.D. 8	18,89 € / Stk

**More Pictures**
