

## Datasheet for: 124856



### Service unit 3-part »variobloc«, Protective cage, Size 1, G 3/8

Service unit 3-part »variobloc«, PC container and protective cage, Size 1, G 3/8, Input pressure max. 16 bar, Temp. max. 50 °C . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | VW 13 S                                                                                            |
| Article number | 124856                                                                                             |
| EAN/barcode    | <br>4047322398374 |
| Your price     | 151,99 € / Stk                                                                                     |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| A                        | 144.0 mm                                                                                    |
| B                        | 201.0 mm                                                                                    |
| Bowl                     | Polycarbonate container with protective cage                                                |
| C                        | 68.0 mm                                                                                     |
| Condensate drain         | Manual                                                                                      |
| Diaphragms               | NBR                                                                                         |
| Filter rating            | 40.0 µm                                                                                     |
| Flow rate                | 1800 l/min                                                                                  |
| Flow rate measurement    | At P <sub>1</sub> = 10 bar, P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar |
| Housing                  | Die-cast zinc                                                                               |
| Max. ambient temperature | 50 °C                                                                                       |
| Max. control range       | 10.0 bar                                                                                    |
| Max. input pressure      | 16 bar                                                                                      |
| Max. medium temperature  | 50 °C                                                                                       |
| Min. control range       | 0.5 bar                                                                                     |
| Page No.                 | WEB                                                                                         |

|                             |           |
|-----------------------------|-----------|
| Pressure gauge display max. | 10.0 bar  |
| Pressure gauge display min. | 0.0 bar   |
| Sealant                     | NBR       |
| Series                      | variobloc |
| Sight dome                  | PA        |
| Size                        | 1         |
| Spring bonnet               | POM       |
| Thread                      | G 3/8     |

## Variants

| Article number | Thread | Flow rate  | Size | Price          |
|----------------|--------|------------|------|----------------|
| 124856         | G 3/8  | 1800 l/min | 1    | 151,99 € / Stk |
| 124860         | G 3/4  | 5000 l/min | 2    | 223,10 € / Stk |
| 124862         | G 1    | 5000 l/min | 2    | 257,58 € / Stk |
| 124858         | G 1/2  | 3400 l/min | 2    | 223,10 € / Stk |
| 124854         | G 1/4  | 1500 l/min | 1    | 151,99 € / Stk |

## More Pictures

