


Datasheet for: 141938

Pushbutton safety coupling I.D. 6, ISO 6150 C, Hose 8x6


Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, Hose 8x6, Operating pressure max. 12 bar, Temp. -20 °C to 200 °C . High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling. After a second push the plug is released. This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded. The safety version meets ISO standard DIN EN ISO 4414. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

Type number	406.31-ES
Article number	141938
EAN/barcode	 4047322566940
Your price	27,44 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Hose connection 8x6
DN	6
Flow rate	1150 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 1$ bar
Housing	Stainless steel
Length	62.0 mm
Max. operating pressure	12 bar
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK577
Page No. SK	SK060
Plug profile	acc. ISO 6150 C
Pushbutton	Stainless steel
Sealant	FKM
Spring	Stainless steel
Threaded piece	Galvanised steel
Valve	Brass

a/f

20 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
141938	Hose connection 8x6	27,44 € / Stk
141939	Hose connection 10x8	27,44 € / Stk

More Pictures

