


Datasheet for: 133183


Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, Rp/R 1

Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, IT/ET, Rp/R 1, DN 25, Operating temp. -15 °C to 60 °C, PN max. 5 bar . Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

Type number	350.1115
Article number	133183
EAN/barcode	 4047322476744
Your price	42,33 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	105.0 mm
B	57.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	25.0
DVGW approval	DIN EN 331:2013-05
Hand lever	Aluminium
Housing	Nickel-plated brass
L	89.0 mm
Operating pressure	max. 5 bar (pressure class MOP 5 acc. to DIN EN 331)
Operating temperature	-15 °C to 60 °C for gas
Page No.	HK289
Standard thread	Thread acc. to ISO 7-1
Stem seal	PTFE / EPDM / HNBR
Thread	Rp/R 1
Thread material	Brass

Variants

Article number	Thread	DN	Price
133183	Rp/R 1	25.0	42,33 € / Stk
133184	Rp/R 1 1/4	32.0	68,31 € / Stk
133179	Rp/R 1/4	8.0	14,40 € / Stk
133185	Rp/R 1 1/2	40.0	98,24 € / Stk
133180	Rp/R 3/8	10.0	15,68 € / Stk
133182	Rp/R 3/4	20.0	28,15 € / Stk
133181	Rp/R 1/2	15.0	18,81 € / Stk
133186	Rp/R 2	50.0	139,26 € / Stk

More Pictures

