


Datasheet for: 103694



Brass ball valve, Electr. actuation drive 230 V AC, 50 Hz, Rp 1/2

Brass ball valve, Electr. actuation drive, 230 V AC, 50 Hz, Operating temperature -20 °C to 70 °C, Rp 1/2, DN 15, PN max. 40 bar . Voltage range 230 VAC, 50 Hz or 24 VDC. 2-way cock, full bore, for neutral gases and liquids. Reversible electric rotary actuator.

Type number	350.1810R
Article number	103694
EAN/barcode	 4047322339162
Your price	563,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	153.0 mm
Actuating time	15 sec.
B	164.5 mm
Ball	Hard chrome-plated brass
Ball seal	PTFE, glass fibre-reinforced
D	17.0 mm
DN	15.0
Duty cycle	30 %
Housing	Aluminium powder-coated
L	75.0 mm
Material	Nickel-plated brass
Max. ambient temperature	70 °C
Max. operating temperature	70 °C
Min. ambient temperature	-30 °C
Min. operating temperature	-20 °C
Mounting flange	ISO 5211
PN	40 bar
Page No.	HK315
Position indicator	Manually operated
Protection IP	IP 68

Relative humidity	30 % to 95 %
Selector shaft	Hard chrome-plated brass
Selector shaft seal	FKM
Thread	Rp 1/2
Voltage	230 VAC, 50 Hz
a/f	26 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103694	Rp 1/2	15.0	40 bar	26 mm	563,91 € / Stk
103695	Rp 3/4	20.0	40 bar	32 mm	565,68 € / Stk
103697	Rp 1 1/4	32.0	40 bar	50 mm	603,52 € / Stk
103698	Rp 1 1/2	40.0	25 bar	55 mm	624,27 € / Stk
103696	Rp 1	25.0	40 bar	41 mm	576,15 € / Stk
103699	Rp 2	50.0	25 bar	70 mm	673,06 € / Stk

More Pictures

