

## Datasheet for: 141956

**Pushbutton safety coupling I.D. 8, ISO 6150 C, G 3/8 ET**


Pushbutton safety coupling I.D. 8, ISO 6150 C, Stainless steel, G 3/8 ET, Operating pressure max. 16 bar, Temp. -20 °C to 200 °C . High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling. After a second push the plug is released. This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded. The safety version meets ISO standard DIN EN ISO 4414. These safety couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

Type number	408.13-ES
-------------	-----------

Article number	141956
----------------	--------

EAN/barcode	 4047322566971
-------------	---

Your price	46,25 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 3/8 ET
DN	8
Flow rate	2080 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 1$ bar
Housing	Stainless steel
Length	72.0 mm
Max. operating pressure	16 bar
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK582
Page No. SK	SK066
Plug profile	acc. ISO 6150 C
Pushbutton	Stainless steel
Sealant	FKM

Spring  
 Threaded piece  
 Valve  
 a/f

Stainless steel  
 Galvanised steel  
 Brass  
 25 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>Price</i>
141956	G 3/8 ET	72.0 mm	46,25 € / Stk
141957	G 1/2 ET	75.0 mm	33,31 € / Stk
141955	G 1/4 ET	72.0 mm	46,25 € / Stk

## More Pictures

