


Datasheet for: 106711



Two-handed safety console, complete, Quick-connect plug hose 4 mm

Two-handed safety console, complete, Quick-connect plug hose 4 mm, Operating pressure 2.5 - 8 bar, Temp. -10 °C to 60 °C. This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position; the valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Type number	SK-85
Article number	106711
EAN/barcode	 4047322350082
Your price	591,96 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Push-in fitting for 4 mm pipe
Description	Complete pushbutton panel with safety valve
Flow rate at 6 bar and Δp 1.0 bar	85 NI/min
Max. operating pressure	8 bar
Max. temperature range	60 °C
Medium	Filtered, unlubricated compressed air
Min. operating pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Pneumatic
Page No.	HK487
Page No. SF	SF054
Synchronisation, max. time between two signals	0.4 sec.