

## Datasheet for: 135104


**Straight push-in fitting, G 1/2 i., for hose exterior Ø 12 mm**

Straight push-in fitting, Exterior hexagonal, G 1/2 i., for hose exterior Ø 12 mm, Working pressure max. 20 bar, Stainless steel . For use in more aggressive environments and corrosive media.

Type number	846.012-12 ES
Article number	135104
EAN/barcode	 4047322493116
Your price	63,71 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For tube O.D.	12 mm
L1	35.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK719
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/2
Working pressure pulsate	10.0 bar
a/f	27 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
135104	G 1/2	12 mm	27 mm	63,71 € / Stk
135096	G 1/4	8 mm	17 mm	33,96 € / Stk
135106	G 1/2	16 mm	27 mm	78,39 € / Stk
135098	G 1/4	12 mm	21 mm	57,01 € / Stk
135105	G 1/2	14 mm	27 mm	70,42 € / Stk
135093	G 1/8	8 mm	16 mm	30,60 € / Stk
135101	G 3/8	12 mm	21 mm	56,17 € / Stk
135094	G 1/4	4 mm	17 mm	28,50 € / Stk
135099	G 3/8	8 mm	21 mm	39,83 € / Stk
135102	G 3/8	14 mm	22 mm	67,07 € / Stk
135095	G 1/4	6 mm	17 mm	28,09 € / Stk
135092	G 1/8	6 mm	13 mm	27,25 € / Stk
135103	G 1/2	10 mm	27 mm	55,33 € / Stk
135100	G 3/8	10 mm	21 mm	47,37 € / Stk
135091	G 1/8	4 mm	13 mm	25,15 € / Stk
135097	G 1/4	10 mm	17 mm	36,89 € / Stk

## More Pictures

