


## Datasheet for: 142187


**Vibration damper with 300 mm PVC hose, plug I.D. 12, G 1/2 ET**

Vibration damper with 300 mm PVC workshop hose, plug I.D. 12, G 1/2 ET, pressed, max. 15 bar, Temp. -20 °C to 60 °C . When using pulsating tools it is recommended to observe the standard ISO 6150, § 7.1. It recommends installing a minimum 300 mm long, flexible hose between the pulsating tool and the quick-connect coupling. The oscillating forces are taken by the hose piece and thus increase the service life of the quick-connect coupling. No warranty can be made for couplings mounted directly on pulsating tools.

Type number	VD-300-12-1/2
Article number	142187
EAN/barcode	 4047322553490
Your price	9,75 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/2 ET
DN	12
Max. operating pressure	15 bar
Max. temperature range	60 °C
Min. temperature range	-20 °C
Page No.	HK924
Page No. SK	SK096

**Variants**

Article number	Connection	DN	Price
142187	G 1/2 ET	12	9,75 € / Stk

## Variants

<i>Article number</i>	<i>Connection</i>	<i>DN</i>	<i>Price</i>
142186	G 1/2 ET	10	10,98 € / Stk
142190	G 1 ET	19	58,90 € / Stk
142182	G 1/4 ET	7.2 - 7.8	13,33 € / Stk
142895	G 1/2 ET	11	10,98 € / Stk
142894	G 3/8 ET	8	20,20 € / Stk