

Datasheet for: 103703


Brass ball valve, Electrical actuation drive, 24 V DC, Rp 1 1/4

Brass ball valve, Electrical actuation drive, 24 V DC, Operating temperature -20 °C to 70 °C, Rp 1 1/4, DN 32, PN max. 40 bar . Voltage range 230 VAC, 50 Hz or 24 VDC. 2-way cock, full bore, for neutral gases and liquids. Reversible electric rotary actuator.

Type number	350.2813R
-------------	-----------

Article number	103703
----------------	--------

EAN/barcode	 4047322339254
-------------	--

Your price	603,52 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	153.0 mm
Actuating time	20 sec.
B	181.5 mm
Ball	Hard chrome-plated brass
Ball seal	PTFE, glass fibre-reinforced
D	30.0 mm
DN	32.0
Duty cycle	30 %
Housing	Aluminium powder-coated
L	110.0 mm
Material	Nickel-plated brass
Max. ambient temperature	70 °C
Max. operating temperature	70 °C
Min. ambient temperature	-30 °C
Min. operating temperature	-20 °C
Mounting flange	ISO 5211
PN	40 bar
Page No.	HK315
Position indicator	Manually operated
Protection IP	IP 68

Relative humidity	30 % to 95 %
Selector shaft	Hard chrome-plated brass
Selector shaft seal	FKM
Thread	Rp 1 1/4
Voltage	24 VDC
a/f	50 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103703	Rp 1 1/4	32.0	40 bar	50 mm	603,52 € / Stk
103700	Rp 1/2	15.0	40 bar	26 mm	563,91 € / Stk
103704	Rp 1 1/2	40.0	25 bar	55 mm	624,27 € / Stk
103705	Rp 2	50.0	25 bar	70 mm	673,06 € / Stk
103702	Rp 1	25.0	40 bar	41 mm	576,15 € / Stk
103701	Rp 3/4	20.0	40 bar	32 mm	565,68 € / Stk

More Pictures

