


Datasheet for: 136360


**Hose reel, PU anti-spark., Hose-ø 9.5x13.5, Length 14 m**

Hose reel for compressed air, PU, anti-spark, Hose-ø 9.5x13.5, Length 14 m, Operating temp. -20 °C to 60 °C, PN max. 12 bar . For simple mounting on the wall or ceiling. Shock resistant, solid and closed housing made of POM, disposal/outflow R 1/4 AG and with light, heavy duty, oil resistant and spark erosion protected polyurethane hose. The hose is resistant to flying sparks and scorching, which can occur in the welding environment or with the use of cutting tools. Incl. 2 m supply hose.

Type number	259/5130
-------------	----------

Article number	136360
----------------	--------

EAN/barcode	 4047322504287
-------------	--



Your price	607,29 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	395.5 mm
Applications	for compressed air
B	453.6 mm
Hose length	14 m
Hose material	braided, spark erosion protected polyurethane
Hose size	9.5x13.5 mm
Max. operating pressure	12 bar
Max. operating temperature	60 °C
Min. operating temperature	-20 °C
Page No.	WEB
Swivel angle	300 °

**More Pictures**

