

Datasheet for: 135285


Straight push-in connector with plug nipple 8 mm, reducing

Straight push-in connector with plug nipple 8 mm, reducing, for hose exterior Ø 6 mm, Working pressure max 20 bar, Stainless steel . For use in more aggressive environments and corrosive media.

Type number	859.0806 ES
Article number	135285
EAN/barcode	 4047322494915
Your price	22,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	6 mm
L1	41.8 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK724
Plug connection	8 mm
Suitable pipe materials	PVDF, PTFE, PA, PU
Working pressure pulsate	10.0 bar

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
135285	6 mm	22,81 € / Stk
135286	6 mm	27,44 € / Stk
135288	8 mm	30,33 € / Stk
135289	10 mm	31,47 € / Stk
135283	4 mm	19,05 € / Stk
135284	4 mm	24,26 € / Stk
135290	12 mm	45,91 € / Stk
135291	12 mm	49,38 € / Stk
135287	8 mm	24,83 € / Stk

More Pictures

