


## Datasheet for: 103707


**Stainless steel ball valve, Electr. actuation drive, Rp 3/4**

2-way stainless steel ball valve, Electr. actuation drive, 230 V AC, 50 Hz, Medium temp. -10 °C to 200 °C, Rp 3/4, PN max. 63 bar . Voltage range 230 VAC, 50 Hz or 24 VDC. Reversible electric rotary actuator.

Type number	350.3811R
Article number	103707
EAN/barcode	 4047322339292
Your price	626,24 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	153.0 mm
Actuating time	15 sec.
B	153.0 mm
Ball seal	PTFE, glass fibre-reinforced
D	17.5 mm
DN	20.0
Duty cycle	30 %
Housing	Aluminium powder-coated
L	80.0 mm
Length	DIN 3203 - M3
Material	Stainless steel 1.4401 / 1.4408
Max. ambient temperature	70 °C
Max. medium temperature	200 °C
Max. operating pressure	63 bar
Min. ambient temperature	-30 °C
Min. medium temperature	-10 °C
Mounting flange	ISO 5211
Page No.	HK316
Position indicator	Manually operated
Protection IP	IP 68

Relative humidity 30 % to 95 %  
 Selector shaft PTFE, glass fibre-reinforced  
 seal  
 Thread Rp 3/4  
 Voltage 230 VAC, 50 Hz  
 a/f 35 mm

## Variants

Article number	Thread	DN	a/f	Price
103707	Rp 3/4	20.0	35 mm	626,24 € / Stk
103709	Rp 1 1/4	32.0	50 mm	690,07 € / Stk
103708	Rp 1	25.0	41 mm	659,44 € / Stk
103706	Rp 1/2	15.0	28 mm	604,22 € / Stk
103710	Rp 1 1/2	40.0	58 mm	763,69 € / Stk
103711	Rp 2	50.0	73 mm	1.111,99 € / Stk

## More Pictures

