

Datasheet for: 135919


Stainless steel ball valve, length acc. to DIN 3202-M3, G 3

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 3, DN 76, Operating temp. -20 °C to 180 °C, PN max. 40 bar .

Type number 3390.10

Article number 135919

EAN/barcode



4047322501613

Your price 637,50 € / Stk

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|--|
| A | 350.0 mm |
| B | 149.0 mm |
| Ball | Stainless steel 1.4401 |
| Ball seal | PTFE (15 % glass fibre reinforced) |
| DN | 76.0 |
| Hand lever | Stainless steel 1.4301, with plastic coating |
| Housing | Stainless steel 1.4408 |
| ISO 5211 | F 07 / F 10 |
| L | 205.0 mm |
| Max. operating temperature | 180 °C |
| Min. operating temperature | -20 °C |
| PN | 40 bar |
| Page No. | HK278 |
| Standard thread | G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211 |
| Stem seal | PTFE |
| Thread | G 3 |

Variants

| Article number | Thread | DN | PN | Price |
|----------------|---------|------|--------|----------------|
| 135919 | G 3 | 76.0 | 40 bar | 637,50 € / Stk |
| 135916 | G 1 1/2 | 38.0 | 63 bar | 140,60 € / Stk |
| 135910 | G 1/4 | 11.6 | 63 bar | 38,20 € / Stk |
| 135911 | G 3/8 | 12.5 | 63 bar | 38,20 € / Stk |
| 135915 | G 1 1/4 | 32.0 | 63 bar | 107,71 € / Stk |
| 135912 | G 1/2 | 15.0 | 63 bar | 48,65 € / Stk |
| 135917 | G 2 | 50.0 | 63 bar | 201,94 € / Stk |
| 135913 | G 3/4 | 20.0 | 63 bar | 59,81 € / Stk |
| 135914 | G 1 | 25.0 | 63 bar | 81,61 € / Stk |
| 135918 | G 2 1/2 | 64.0 | 40 bar | 469,70 € / Stk |

More Pictures

