

Datasheet for: 135928


3-way ball valve, T-hole, Stainless steel 1.4408, G 1/4, DN 11

3-way ball valve, T-hole, Stainless steel 1.4408, G 1/4, DN 11, Operating temperature -20 °C to 180 °C, PN max. 63 bar . With L or T-bore, reduced bore. Version for sealing on all sides with integrated ISO flange plate (ISO 5211). The lever can be turned 360° to allow several switching variants.

Type number	11082 A-ES
-------------	------------

Article number	135928
----------------	--------

EAN/barcode



4047322501705

Your price	115,09 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	112.0 mm
B	77.5 mm
Ball	Stainless steel 1.4401
Ball seal	RTFE (15 % glass fibre reinforced PTFE)
C Ø	11.0 mm
DN	11.0
Hand lever	Stainless steel 1.4301, with plastic coating
Housing	Stainless steel 1.4408
ISO 5211	F 04
L	75.7 mm
Material	Stainless steel 1.4408
Max. operating pressure	63 bar
Max. operating temperature	180 °C
Min. operating temperature	-20 °C
Operating pressure	63 bar (dependent on temperature)
Page No.	HK297
Sealant	RTFE
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	RTFE (15 % glass fibre reinforced PTFE)
Thread	G 1/4

Variants

Article number	Thread	DN	C Ø	Price
135928	G 1/4	11.0	11.0 mm	115,09 € / Stk
103471	G 1/2	15.0	12.5 mm	113,88 € / Stk
103472	G 3/4	20.0	16.0 mm	146,35 € / Stk
103473	G 1	25.0	20.0 mm	185,59 € / Stk
103474	G 1 1/4	32.0	25.0 mm	275,85 € / Stk
103475	G 1 1/2	40.0	31.8 mm	323,00 € / Stk
103476	G 2	50.0	38.1 mm	485,86 € / Stk
135931	G 3/4	16.0	16.0 mm	150,74 € / Stk
135929	G 3/8	11.0	11.0 mm	115,09 € / Stk
135930	G 1/2	12.7	12.7 mm	117,30 € / Stk
135932	G 1	20.0	20.0 mm	191,16 € / Stk
135934	G 1 1/2	32.0	32.0 mm	332,69 € / Stk

More Pictures

