


Datasheet for: 135972


**Bulkhead fitting POM, G 3/8, for hose exterior Ø 4 mm**

Bulkhead fitting POM, G 3/8, for hose exterior Ø 4 mm, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	71.038-4
Article number	135972
EAN/barcode	 4047322500661
Your price	3,13 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

For tube O.D.	4 mm
L1	35.2 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	16 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK694
Thread	G 3/8
a/f	19 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>Price</i>
135972	G 3/8	4 mm	3,13 € / Stk
110324	G 3/8	6 mm	3,33 € / Stk
110325	G 1/2	8 mm	3,45 € / Stk
135974	G 1/2	10 mm	6,76 € / Stk
135975	G 3/4	12 mm	8,30 € / Stk
135973	G 3/8	5 mm	3,25 € / Stk

## More Pictures

