


Datasheet for: 136116


Rem. double threaded nipple, con. sealing, R 3/8 o., R 3/8 o., Brass

Rem. double threaded nipple, conical sealing, R 3/8 o., R 3/8 o., Brass, Max. working pressure 25 bar, Max. operating temp. 150 °C .

Type number	MS252L3838
Article number	136116
EAN/barcode	 4047322502443
Your price	4,09 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

L1	37.0 mm
Material	Brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	HK767
Thread 1	R 3/8
Thread 2	R 3/8
a/f	22 mm
a/f 1	8.0 mm

Variants

Article number	Thread 1	Thread 2	a/f	a/f 1	Price
136116	R 3/8	R 3/8	22 mm	8.0 mm	4,09 € / Stk
111194	R 1/8	R 1/8	15 mm	5.0 mm	2,16 € / Stk
111196	R 1/4	R 1/4	19 mm	6.0 mm	2,56 € / Stk

Variants

Article number	Thread 1	Thread 2	a/f	a/f 1	Price
111198	R 3/8	R 3/8	22 mm	8.0 mm	4,06 € / Stk
111199	R 1/2	R 1/2	27 mm	12.0 mm	4,63 € / Stk
111200	R 3/4	R 3/4	36 mm	14.0 mm	11,99 € / Stk
111201	R 1	R 1	46 mm	19.0 mm	21,60 € / Stk
111195	R 1/8	R 1/4	15 mm	5.0 mm	2,49 € / Stk
111197	R 1/4	R 3/8	19 mm	6.0 mm	3,64 € / Stk
136121	R 1 1/2	R 1 1/2	70 mm	24.0 mm	74,62 € / Stk
136120	R 1 1/4	R 1 1/4	60 mm	22.0 mm	50,59 € / Stk
136122	R 2	R 2	80 mm	32.0 mm	108,59 € / Stk
136118	R 3/4	R 3/4	36 mm	14.0 mm	10,59 € / Stk
136113	R 1/8	R 1/4	15 mm	5.0 mm	2,10 € / Stk
136119	R 1	R 1	50 mm	19.0 mm	23,00 € / Stk
136112	R 1/8	R 1/8	15 mm	5.0 mm	1,91 € / Stk
136114	R 1/4	R 1/4	19 mm	6.0 mm	2,61 € / Stk
136117	R 1/2	R 1/2	27 mm	12.0 mm	4,76 € / Stk
136115	R 1/4	R 3/8	19 mm	6.0 mm	3,58 € / Stk