


## Datasheet for: 142519


**Ball valve 3/2-way »FUTURA-mini«, lockable, Size 0, G 1/4**

Ball valve 3/2-way »FUTURA-mini«, lockable, Size 0, G 1/4, Exhaust G 1/4, Input pressure max. 12 bar, Temperature -10 °C to 50 °C . Lockable ball valve, 3/2-way type including silencer, mechanically operated. Rotary switch can be turned 90°, with indication of positions: Horizontal: Input closed - outlet exhausted Vertical: Flow open - exhaust closed Exhaust air can be collected.

Type number	FUM 951
Article number	142519
EAN/barcode	 4047322557443
Your price	26,76 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	43.0 mm
B	87.0 mm
C	51.0 mm
Connecting thread	Plastic
Exhaust air	G 1/4
Flow rate	2300 l/min
Flow rate measurement	At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Housing	PA66 GF60
Max. input pressure	12 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. temperature range	-10 °C
Page No.	HK022
Series	FUTURA-mini
Thread	G 1/4

**More Pictures**

