


Datasheet for: 142521


3/2-way valve »FUTURA-mini«, electr. actuated, 24 V AC, G 1/4

3/2-way valve »FUTURA-mini«, electr. actuated with solenoid 24 V AC, 50 Hz, Size 0, G 1/4, Exhaust G 1/4, Input press. 2.5-10 bar . Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. 3/2-way type including silencer. When they are switched off, the system is exhausted at the same time.

Type number	FUM 923-AC
Article number	142521
EAN/barcode	 4047322557467
Your price	90,11 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	43.0 mm
B	138.0 mm
C	93.0 mm
Connecting thread	Plastic
Duty cycle	100 %
Electrical connection	Socket coupling EN 175301-803, form C, poles 2+PE
Exhaust air	G 1/4
Flow rate	2000 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ_p = 1 bar
Holding power with 50 Hz AC voltage	1.6 VA
Housing	PA66 GF60
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.5 bar
Min. temperature range	-10 °C
Page No.	HK023

Pick-up power
with 50 Hz AC
voltage
Power input
Protection IP
Series
Thread

2.2 VA

2.5 Watt with DC voltage
IP 65
FUTURA-mini
G 1/4

More Pictures

