


## Datasheet for: 142529


**Filling unit »FUTURA-mini«, pneumatically actuated, Size 0, G 1/4**

Filling unit »FUTURA-mini«, pneumatically actuated, Size 0, G 1/4, Exhaust G 1/4, Input pressure 2.5 - 12 bar, Temp. -10°C to 50°C . The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure. The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve). It is connected and disconnected by means of the 3/2-way valve. The filling time can be altered by turning the adjusting screw.

Type number	FUM 919
Article number	142529
EAN/barcode	 4047322557542
Your price	106,91 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	86.0 mm
B	105.0 mm
C	60.0 mm
Connecting thread	Plastic
Flow rate	1400 l/min
Flow rate measurement	At P <sub>2</sub> = 6 bar and pressure drop $\Delta_p$ = 1 bar
Housing	PA66 GF60
Max. input pressure	12 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.5 bar
Min. temperature range	-10 °C
Page No.	HK026
Series	FUTURA-mini
Thread	G 1/4

**More Pictures**

