

Datasheet for: 142530


Filling unit »FUTURA-mini«, electr. actuated, 24 V AC/50 Hz, G1/4

Filling unit »FUTURA-mini«, electr. actuated with solenoid 24 V AC, 50 Hz, Size 0, G 1/4, Exhaust G 1/4, Input pr. 2.5 - 10 bar . The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure. The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve). It is connected and disconnected by means of the 3/2-way valve. The filling time can be altered by turning the adjusting screw.

Type number	FUM 913-AC
-------------	------------

Article number	142530
----------------	--------



Your price	141,45 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	86.0 mm
B	138.0 mm
C	93.0 mm
Connecting thread	Plastic
Duty cycle	100 %
Electrical connection	Socket coupling EN 175301-803, form C, poles 2+PE
Exhaust air	G 1/4
Flow rate	1400 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop $\Delta_p = 1$ bar
Holding power with 50 Hz AC voltage	1.6 VA
Housing	PA66 GF60
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.5 bar
Min. temperature range	-10 °C
Page No.	HK025

Pick-up power
with 50 Hz AC
voltage
Power input
Protection IP
Series
Thread

2.2 VA

2.5 Watt with DC voltage
IP 65
FUTURA-mini
G 1/4

More Pictures

