

Datasheet for: 101559



Pre-filter without differential pressure gauge, 3 µm, G 2

Pre-filter without differential pressure gauge, 3 µm, G 2, Input pressure 4 - 16 bar, Medium / ambient temperature 5 °C to 60 °C . For filtering out solid impurities larger than 3 µm and for moisture separation. For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

Type number	429.5612
Article number	101559
EAN/barcode	 4047322086448
Your price	643,79 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	118.0 mm
B2	810.0 mm
C	72.0 mm
D	1238.0 mm
Efficiency	99.99 %
Filter element	Polyethylene (with 45% cavity)
Filter rating	3.0 µm
Flow rate	13000 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p = 0.5%
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. ambient temperature	5 °C
Min. input pressure	4.0 bar
Min. medium temperature	5 °C
Page No.	HK137
Particle separation	from 3 µm

Thread
 filter bowl

 G 2
 Aluminium

Variants

Article number	Thread	Flow rate	Price
101559	G 2	13000 l/min	643,79 € / Stk
101552	G 1/4	1000 l/min	241,67 € / Stk
101553	G 3/8	1000 l/min	240,53 € / Stk
101554	G 1/2	1000 l/min	241,67 € / Stk
101555	G 3/4	2000 l/min	279,51 € / Stk
101556	G 1	3000 l/min	407,20 € / Stk
101557	G 1 1/4	5300 l/min	466,62 € / Stk
101558	G 1 1/2	8300 l/min	513,92 € / Stk

More Pictures

