


## Datasheet for: 102978


**2/2-way sol. valve,AISI 304,FKM,NC, force pilot op.,230 V,G 1/2**

2/2-way sol. valve,AISI 304,FKM,NC,force pilot op., 230 V,50-60 Hz,med. temp. -20°C - 100°C,amb.temp.-20°C - 50°C,G 1/2,PN 0-9 bar . Available versions - Directly operated - Combined operation

Type number	MV 122 ES
Article number	102978
EAN/barcode	 4047322157520
Your price	665,44 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	80.0 mm
B	71.0 mm
DN	16.0
Electrical connection	For Pg 11P connector socket acc. to DIN 4400
Function	normally closed (NC)
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. ambient temperature	50 °C
Max. medium temperature	100 °C
Max. operating pressure	9 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK328
Protection IP	IP65 (with connector socket fitted)
Sealant	FKM
Thread	G 1/2
Type	3
Valve seat	Stainless steel 1.4301

## Variants

Article number	Thread	Max. medium temperature	Sealant	Price
102978	G 1/2	100 °C	FKM	665,44 € / Stk
102977	G 1/2	85 °C	NBR	604,45 € / Stk
102979	G 3/4	85 °C	NBR	651,75 € / Stk

## More Pictures

