

Datasheet for: 151525


Straight Check valve »Blue Series«, Hose to thread, R 3/8 O.

Straight Check valve »Blue Series«, Hose to thread, R 3/8 o., for hose exterior Ø 12 mm, Working pressure max. 10 bar . The non-return function of these push-in fittings prevents the air from flowing back, the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

Type number	203.3812-2
Article number	151525
EAN/barcode	 4047322593816
Your price	9,97 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	Air, vacuum
For tube O.D.	12 mm
L1	44.5 mm
Material	Plastic and nickel-plated brass
Max. temperature range	60 °C
Max. working pressure	10 bar
Medium	Compressed air
Min. opening pressure	0.2 bar
Page No.	HK689
Recommended hose	PU or PA (nylon)
Series	Blue series
Sleeve	Plastic blue
Standard thread	ISO 7-1
Thread a/f	R 3/8 21 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
151525	R 3/8	12 mm	21 mm	9,97 € / Stk
151523	R 1/4	8 mm	14 mm	6,92 € / Stk
151526	R 1/2	10 mm	21 mm	12,04 € / Stk
151521	R 1/8	8 mm	14 mm	5,01 € / Stk
151527	R 1/2	12 mm	21 mm	13,50 € / Stk
151524	R 3/8	10 mm	17 mm	8,64 € / Stk
151520	R 1/8	6 mm	12 mm	4,03 € / Stk
151522	R 1/4	6 mm	14 mm	6,83 € / Stk
151519	R 1/8	4 mm	10 mm	3,98 € / Stk

More Pictures

