


Datasheet for: 151733


Stainless steel safety ball valve, lockable, Venting hole, G 3/4

Stainless steel safety ball valve, lockable, Venting hole M5, Operating temp. -20 °C to 160 °C, G 3/4, DN 20, PN max. 17 bar . Stainless steel safety ball valves. Specially designed for pneumatic applications. The ball valve can be locked manually and has a relief port.

| | |
|----------------|--|
| Type number | 3396.05 |
| Article number | 151733 |
| EAN/barcode |  4047322595223 |
| Your price | 68,55 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|---|
| A | 123.0 mm |
| B | 60.5 mm |
| Ball | Stainless steel 1.4408 |
| Ball seal | PTFE |
| DN | 20.0 |
| Hand lever | Stainless steel 1.4301, PVC coated |
| Housing | Stainless steel 1.4408 |
| L | 75.0 mm |
| Max. operating pressure | 17 bar |
| Max. operating temperature | 160 °C |
| Min. operating temperature | -20 °C |
| Note | The images maybe different from the original part |
| Page No. | HK282 |
| Relief port | M5 |
| Standard thread | G thread acc. to DIN EN ISO 228-1 |
| Stem seal | PTFE |
| Thread | G 3/4 |

Variants

| Article number | Thread | DN | Price |
|----------------|--------|------|---------------|
| 151733 | G 3/4 | 20.0 | 68,55 € / Stk |
| 151732 | G 1/2 | 15.0 | 51,09 € / Stk |
| 151734 | G 1 | 25.0 | 90,22 € / Stk |
| 151731 | G 3/8 | 12.5 | 49,82 € / Stk |
| 151730 | G 1/4 | 11.5 | 48,10 € / Stk |

More Pictures

