


Datasheet for: 156019


Removable Double threaded nipple, conical sealing, R 1 o., R 1 o.

Rem. Double threaded nipple, con. seal. R 1 o., R 1 o. nickel-plated brass, Max. working pressure 25 bar, Max. operating temp. 150°C . **As long as stock lasts. Subject to prior sale. Due to stock clearing, the items are excluded from return. The warranty obligation is not affected. Dimensions may vary slightly.**

| | |
|----------------|--|
| Type number | MSN252L11G |
| Article number | 156019 |
| EAN/barcode |  4047322623957 |
| Your price | 5,12 € / Stk |

Minimum order quantity

| | |
|------------------------|------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 St |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|----------------------------|
| L1 | 59.0 mm |
| Material | Nickel-plated brass CW614N |
| Max. operating temperature | 150 °C |
| Max. working pressure | 25 bar |
| Page No. | WEB |
| Thread 1 | R 1 |
| Thread 2 | R 1 |
| a/f | 50 mm |

Variants

| Article number | Thread 1 | Thread 2 | a/f | Price |
|----------------|----------|----------|-------|---------------|
| 156019 | R 1 | R 1 | 50 mm | 5,12 € / Stk |
| 156022 | R 2 | R 2 | 80 mm | 15,00 € / Stk |
| 156014 | R 1/4 | R 3/8 | 19 mm | 0,95 € / Stk |

Variants

| <i>Article number</i> | <i>Thread 1</i> | <i>Thread 2</i> | <i>a/f</i> | <i>Price</i> |
|-----------------------|-----------------|-----------------|------------|---------------|
| 156015 | R 3/8 | R 3/8 | 22 mm | 1,05 € / Stk |
| 156017 | R 3/4 | R 3/4 | 36 mm | 4,79 € / Stk |
| 156021 | R 1 1/2 | R 1 1/2 | 70 mm | 15,76 € / Stk |
| 156020 | R 1 1/4 | R 1 1/4 | 60 mm | 9,58 € / Stk |
| 156012 | R 1/8 | R 1/4 | 15 mm | 0,66 € / Stk |