

## Datasheet for: 103715


**Stainless steel ball valve, Electr. actuation drive, 24 V DC**

2-way stainless steel ball valve, Electr. actuation drive, 24 V DC, Medium temp. -10°C to 200°C, Rp 1 1/4, DN 32, PN max. 63 bar . Voltage range 230 VAC, 50 Hz or 24 VDC. Reversible electric rotary actuator.

|             |           |
|-------------|-----------|
| Type number | 350.4813R |
|-------------|-----------|

|                |        |
|----------------|--------|
| Article number | 103715 |
|----------------|--------|

EAN/barcode



4047322339377

|            |                |
|------------|----------------|
| Your price | 690,07 € / Stk |
|------------|----------------|

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                          |                                 |
|--------------------------|---------------------------------|
| A                        | 153.0 mm                        |
| Actuating time           | 20 sec.                         |
| B                        | 159.5 mm                        |
| Ball seal                | PTFE, glass fibre-reinforced    |
| D                        | 25.0 mm                         |
| DN                       | 32.0                            |
| Duty cycle               | 30 %                            |
| Housing                  | Aluminium powder-coated         |
| L                        | 110.0 mm                        |
| Length                   | DIN 3203 - M3                   |
| Material                 | Stainless steel 1.4401 / 1.4408 |
| Max. ambient temperature | 70 °C                           |
| Max. medium temperature  | 200 °C                          |
| Max. operating pressure  | 63 bar                          |
| Min. ambient temperature | -30 °C                          |
| Min. medium temperature  | -10 °C                          |
| Mounting flange          | ISO 5211                        |
| Page No.                 | HK316                           |
| Position indicator       | Manually operated               |

|                     |                              |
|---------------------|------------------------------|
| Protection IP       | IP 68                        |
| Relative humidity   | 30 % to 95 %                 |
| Selector shaft seal | PTFE, glass fibre-reinforced |
| Thread              | Rp 1 1/4                     |
| Voltage             | 24 VDC                       |
| a/f                 | 50 mm                        |

## Variants

| Article number | Thread   | DN   | a/f   | Price            |
|----------------|----------|------|-------|------------------|
| 103715         | Rp 1 1/4 | 32.0 | 50 mm | 690,07 € / Stk   |
| 103714         | Rp 1     | 25.0 | 41 mm | 659,44 € / Stk   |
| 103713         | Rp 3/4   | 20.0 | 35 mm | 626,24 € / Stk   |
| 103712         | Rp 1/2   | 15.0 | 28 mm | 604,22 € / Stk   |
| 103716         | Rp 1 1/2 | 40.0 | 58 mm | 763,69 € / Stk   |
| 103717         | Rp 2     | 50.0 | 73 mm | 1.111,99 € / Stk |

## More Pictures

