


## Datasheet for: 101263


**High performance pressure regulator, G 2, 0.1 - 3 bar**

High performance pressure regulator with 2 pressure gauges, G 2, Control range 0.1 - 3 bar, Input pressure max. 25 bar . Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design for very high flow rates. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the knob down.

Type number	637.201
Article number	101263
EAN/barcode	 4047322107839
Your price	735,87 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	160.0 mm
B	261.0 mm
DN	50.0
Flow rate	50000 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	3.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.1 bar
Page No.	HK162
Pressure gauge display max.	4.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Thread	G 2

## Variants

Article number	Thread	Min. control range	Max. control range	Price
101263	G 2	0.1 bar	3.0 bar	735,87 € / Stk
101259	G 1 1/2	0.1 bar	3.0 bar	799,46 € / Stk
101260	G 1 1/2	0.2 bar	6.0 bar	799,46 € / Stk
101261	G 1 1/2	0.5 bar	10.0 bar	799,46 € / Stk
101262	G 1 1/2	0.5 bar	16.0 bar	799,46 € / Stk
101264	G 2	0.2 bar	6.0 bar	735,87 € / Stk
101265	G 2	0.5 bar	10.0 bar	735,87 € / Stk
101266	G 2	0.5 bar	16.0 bar	735,87 € / Stk

## More Pictures

