


Datasheet for: 101265


High performance pressure regulator, G 2, 0.5 - 10 bar

High performance pressure regulator with 2 pressure gauges, G 2, Control range 0.5 - 10 bar, Input pressure max. 25 bar . Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design for very high flow rates. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the knob down.

Type number	637.203
Article number	101265
EAN/barcode	 4047322107884
Your price	735,87 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	160.0 mm
B	261.0 mm
DN	50.0
Flow rate	50000 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK162
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Thread	G 2

Variants

Article number	Thread	Min. control range	Max. control range	Price
101265	G 2	0.5 bar	10.0 bar	735,87 € / Stk
101259	G 1 1/2	0.1 bar	3.0 bar	799,46 € / Stk
101260	G 1 1/2	0.2 bar	6.0 bar	799,46 € / Stk
101261	G 1 1/2	0.5 bar	10.0 bar	799,46 € / Stk
101262	G 1 1/2	0.5 bar	16.0 bar	799,46 € / Stk
101263	G 2	0.1 bar	3.0 bar	735,87 € / Stk
101264	G 2	0.2 bar	6.0 bar	735,87 € / Stk
101266	G 2	0.5 bar	16.0 bar	735,87 € / Stk

More Pictures

