


Datasheet for: 158062


3/2-way solenoid valve, Stainless steel, NC, 230 V AC, NBR, G 1/4

3/2-way solenoid valve, Stainless steel, NC, Directly oper., 230 V AC, 50-60 Hz, Medium temp. -25 °C to 90 °C, NBR, G 1/4, PN 0-10 bar .

Type number	MV14ES230
Article number	158062
EAN/barcode	 4047322631723
Your price	197,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	95.0 mm
B	40.0 mm
DN	3.2
Electrical connection	for connector socket PG 11 P, acc. to DIN 4400
Function	NC
Housing	Stainless steel
Internal parts	Stainless steel
Max. ambient temperature	55 °C
Max. medium temperature	90 °C
Max. operating pressure	10 bar
Min. ambient temperature	-25 °C
Min. medium temperature	-25 °C
Page No.	HK332
Protection IP	IP 65 (with connector socket fitted)
Sealant	NBR
Thread	G 1/4
Voltage	230 V AC, 50 - 60 Hz

Variants

Article number	Voltage	Price
158062	230 V AC, 50 - 60 Hz	197,54 € / Stk
158061	24 V DC	197,54 € / Stk

More Pictures

