

Datasheet for: 158067


Check valve, DN 32, Brass, G 1 1/4, PN max. 10 bar

Check valve, DN 32, Brass, Metallic sealing, Operating temperature °C to 90 °C, G 1 1/4, PN max. 10 bar .
 Applications: Water (no steam), neutral and non-corrosive liquid media, mineral oils. Only suitable for liquid media.
 Flap valve closes by gravity, therefore only possible to be installed horizontally!

Type number	RK114MSE
Article number	158067
EAN/barcode	 4047322631518
Your price	25,68 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

DN	32.0
Housing	Brass
Length	72.0 mm
Max. operating pressure	10 bar
Max. operating temperature	90 °C
Page No.	HK358
Standard thread	G-thread acc. to DIN EN ISO 228-1
Thread	G 1 1/4
Valve disc	Brass
a/f	50 mm

Variants

Article number	Thread	DN	a/f	Price
158067	G 1 1/4	32.0	50 mm	25,68 € / Stk
158065	G 3/4	20.0	34 mm	11,60 € / Stk

Variants

Article number	Thread	DN	a/f	Price
158068	G 1 1/2	40.0	57 mm	33,48 € / Stk
158070	G 2 1/2	65.0	85 mm	95,99 € / Stk
158064	G 1/2	15.0	27 mm	8,43 € / Stk
158063	G 3/8	10.0	27 mm	9,16 € / Stk
158066	G 1	25.0	42 mm	17,26 € / Stk
158071	G 3	80.0	98.5 mm	132,36 € / Stk
158072	G 4	100.0	126 mm	238,90 € / Stk
158069	G 2	50.0	69 mm	46,95 € / Stk

More Pictures

