

Datasheet for: 158081


Check valve, DN 15, Brass, Soft sealed, G 1/2, PN max. 16 bar

Check valve, DN 15, Brass, Soft sealed, Operating temperature °C to 90 °C, G 1/2, PN max. 16 bar . Applications: Water (no steam), neutral and non-corrosive liquid media, mineral oils. Only suitable for liquid media. Flap valve closes by gravity, therefore only possible to be installed horizontally!

Type number	RK12MSNBRE
Article number	158081
EAN/barcode	 4047322631655
Your price	8,69 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

DN	15.0
Housing	Brass
Length	43.0 mm
Max. operating pressure	16 bar
Max. operating temperature	90 °C
Page No.	HK359
Sealant	NBR
Standard thread	G-thread acc. to DIN EN ISO 228-1
Thread	G 1/2
Valve disc	Brass
a/f	27 mm

Variants

Article number	Thread	DN	a/f	Price
158081	G 1/2	15.0	27 mm	8,69 € / Stk

Variants

Article number	Thread	DN	a/f	Price
158085	G 1 1/2	40.0	57 mm	34,14 € / Stk
158088	G 3/8	10.0	27 mm	9,43 € / Stk
158083	G 1	25.0	42 mm	17,62 € / Stk
158082	G 3/4	20.0	34 mm	11,96 € / Stk
158086	G 2	50.0	69 mm	47,84 € / Stk
158084	G 1 1/4	32.0	50 mm	26,23 € / Stk

More Pictures

