


Datasheet for: 100604



Service station SAFETY »multifix«, Size 5, G 1

Service station SAFETY »multifix«, Ball valve - start-up valve - 2-part service unit, Size 5, G 1, Input pressure 2 - 16 bar . These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Type number	WS 3003
Article number	100604
EAN/barcode	 4047322245678
Your price	851,18 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	410.8 mm
B	382.8 mm
C	157.0 mm
Condensate drain	Semi-automatic
Diaphragms	NBR
Filter element	Cellpor (PE)
Filter rating	5.0 μ m
Flow rate	9800 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Housing	Die-cast zinc
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. temperature range	60 °C
Medium	Compressed air
Min. control range	2.0 bar
Min. input pressure	2.0 bar
Page No.	HK095
Page No. SF	SF026
Pressure gauge display max.	16.0 bar

Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	multifix
Size	5
Spring bonnet	POM
Thread	G 1
Vent port	Silencer (ball valve)

Variants

Article number	Thread	Flow rate	Size	Price
100604	G 1	9800 l/min	5	851,18 € / Stk
100602	G 1/4	1000 l/min	1	291,33 € / Stk
100603	G 1/2	3550 l/min	3	383,83 € / Stk

More Pictures

