


## Datasheet for: 101208


**Stainless steel filter regulator, 1.4404, G 1/2, 1 - 15 bar**

Stainless steel filter regulator, 1.4404, with secondary venting (reversible), incl. press. gauge, G 1/2, Control range 1 - 15 bar . Stainless steel filter regulators with self-relieving (not for liquid media) containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Type number	572.12 D
Article number	101208
EAN/barcode	 4047322101936
Your price	892,54 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	80.0 mm
B	260.0 mm
C	127.0 mm
Condensate drain	Manual drain valve
Diaphragms	PTFE on NBR-carrier
Filter rating	50.0 $\mu$ m
Flow rate	2500 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 5$ bar and pressure drop $\Delta_p \leq 1$ bar
Housing	Stainless steel 1.4404 (AISI 316L)
Max. ambient temperature	60 °C
Max. control range	15.0 bar
Max. input pressure	30 bar
Max. medium temperature	130 °C
Min. control range	1.0 bar
Page No.	HK149
Sealant	FKM
Thread	G 1/2

## Variants

Article number	Thread	Price
101208	G 1/2	892,54 € / Stk
101207	G 1/4	720,25 € / Stk

## More Pictures

