

Datasheet for: 158766


Stainless steel ball valve, Pneumatic actuation drive, Rp 2

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 2, PN max. 40 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.525-1
-------------	-----------

Article number	158766
----------------	--------

EAN/barcode



4047322635264

Your price	701,48 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	393.7 mm
Angle of rotation	90 °
B	255.4 mm
DN	50.0
L	125.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Max. Operating pressure ball valve	150 °C
Max. operating temperature actuator	80 °C
Max. pilot pressure actuator	8.4 bar
Min. Operating pressure ball valve	-20 °C
Min. operating temperature actuator	-20 °C
PN	40 bar
Page No.	HK304
Recommended pilot pressure	5.6 bar
Sealant actuator	NBR

Sealant ball valve
 Thread
 Valve adapter
 Version

PTFE / FKM
 Rp 2
 Integrated to NAMUR
 single-acting - spring to close

Variants

Article number	Thread	DN	PN	Price
158766	Rp 2	50.0	40 bar	701,48 € / Stk
158760	Rp 3/8	10.0	100 bar	272,84 € / Stk
158763	Rp 1	25.0	100 bar	363,00 € / Stk
158761	Rp 1/2	15.0	100 bar	276,75 € / Stk
158762	Rp 3/4	20.0	100 bar	337,50 € / Stk
158764	Rp 1 1/4	32.0	64 bar	431,25 € / Stk
158765	Rp 1 1/2	40.0	64 bar	510,27 € / Stk

More Pictures

