

## Datasheet for: 103717



### Stainless steel ball valve, Electr. actuation drive, 24 V DC

2-way stainless steel ball valve, Electr. actuation drive, 24 V DC, Medium temp. -10 °C to 200 °C, Rp 2, DN 50, PN max. 63 bar . Voltage range 230 VAC, 50 Hz or 24 VDC. Reversible electric rotary actuator.

Type number	350.4815R
-------------	-----------

Article number	103717
----------------	--------

EAN/barcode	
-------------	--



Your price	1.111,99 € / Stk
------------	------------------

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

A	153.0 mm
Actuating time	30 sec.
B	201.0 mm
Ball seal	PTFE, glass fibre-reinforced
D	36.5 mm
DN	50.0
Duty cycle	30 %
Housing	Aluminium powder-coated
L	140.0 mm
Length	DIN 3203 - M3
Material	Stainless steel 1.4401 / 1.4408
Max. ambient temperature	70 °C
Max. medium temperature	200 °C
Max. operating pressure	63 bar
Min. ambient temperature	-30 °C
Min. medium temperature	-10 °C
Mounting flange	ISO 5211
Page No.	HK316
Position indicator	Manually operated

Protection IP	IP 68
Relative humidity	30 % to 95 %
Selector shaft seal	PTFE, glass fibre-reinforced
Thread	Rp 2
Voltage	24 VDC
a/f	73 mm

## Variants

Article number	Thread	DN	a/f	Price
103717	Rp 2	50.0	73 mm	1.111,99 € / Stk
103714	Rp 1	25.0	41 mm	659,44 € / Stk
103713	Rp 3/4	20.0	35 mm	626,24 € / Stk
103712	Rp 1/2	15.0	28 mm	604,22 € / Stk
103716	Rp 1 1/2	40.0	58 mm	763,69 € / Stk
103715	Rp 1 1/4	32.0	50 mm	690,07 € / Stk

## More Pictures

