


## Datasheet for: 154072



### Stainless steel ball valve, Pneumatic actuation drive, Rp 1/2

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 100 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.510-1
Article number	154072
EAN/barcode	 4047322612746
Your price	229,93 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

A	114.0 mm
Angle of rotation	90 °
B	139.0 mm
DN	15.0
L	61.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Max. operating temperature	150 °C
Max. pilot pressure	5.6 bar
Max. temperature range	80 °C
Min. operating temperature	-20 °C
Min. temperature range	-20 °C
PN	100 bar
Page No.	WEB
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1/2
Valve adapter	Supplied as standard
Version	double-acting

## Variants

Article number	Thread	DN	PN	Price
154072	Rp 1/2	15.0	100 bar	229,93 € / Stk
103581	Rp 3/8	10.0	160 bar	226,30 € / Stk
103582	Rp 1/2	15.0	160 bar	229,93 € / Stk
103583	Rp 3/4	20.0	100 bar	276,20 € / Stk
103584	Rp 1	25.0	100 bar	302,63 € / Stk
103585	Rp 1 1/4	32.0	64 bar	345,05 € / Stk
103586	Rp 1 1/2	40.0	64 bar	410,72 € / Stk
103587	Rp 2	50.0	40 bar	544,12 € / Stk
154071	Rp 3/8	10.0	100 bar	233,09 € / Stk

## More Pictures

