


Datasheet for: 102758


Calibration test and service equipment, -0.95 / 40 bar, G 1/4

Calibration test and service equipment, Measurement range -0.95 / +40 bar, G 1/4, incl. factory calibration certificate . Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

| | |
|----------------|--|
| Type number | KTS-40 |
| Article number | 102758 |
| EAN/barcode |  4047322354820 |
| Your price | 1.446,24 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|--------------------------|
| Accuracy | 0.25% FS |
| Connection | G 1/4 |
| Housing | Die-cast zinc |
| Max. ambient temperature | 50 °C |
| Max. medium temperature | 80 °C |
| Measuring range max. bar | 40.0 |
| Measuring range min. bar | -0.95 |
| Min. ambient temperature | -10 °C |
| Min. medium temperature | -20 °C |
| Page No. | HK237 |
| Page No. SF | SF037 |
| Wetted parts | CrNi steel with NBR seal |