

Datasheet for: 159988


Hose reel, PU anti-spark., Hose-ø 9.5x13.5, Length 14 m

Hose reel for compressed air, PU, anti-spark, Hose-ø 9.5x13.5, Length 14 m, Operating temp. -20 °C to 60 °C, PN max. 12 bar . For simple mounting on the wall or ceiling. Shock resistant, solid and closed housing made of POM, disposal/outflow R 1/4 AG and with light, heavy duty, oil resistant and spark erosion protected polyurethane hose. The hose is resistant to flying sparks and scorching, which can occur in the welding environment or with the use of cutting tools. Incl. 1.5 m supply hose.

Type number	259/5130-1
Article number	159988
EAN/barcode	 4047322645171
Your price	607,29 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	490.0 mm
Applications	for compressed air
B	409.0 mm
Hose length	14 m
Hose material	braided, spark erosion protected polyurethane
Hose size	9.5x13.5 mm
Max. operating pressure	12 bar
Max. operating temperature	60 °C
Min. operating temperature	-20 °C
Page No.	HK927
Swivel angle	180 °

More Pictures

