

Datasheet for: 137345



Stainless steel casting filter regulator, G 1 1/2, 0.4 - 4.0 bar

Stainless steel casting filter regulator, 1.4401, secondary venting (reversible), Size 4, G 1 1/2, Control range 0.4 - 4.0 bar . Stainless steel filter regulators with self-relieving (not for liquid media) for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc. Pressure setting by T-handle.

Type number	580FRC4-112-4
Article number	137345
EAN/barcode	 4047322513289
Your price	2.035,48 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	120.0 mm
B	301.0 mm
C	136.0 mm
Condensate drain	Manual drain valve
Diaphragms	NBR/PTFE
Filter rating	25.0 μ m
Flow rate	11330 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar
Housing	Stainless steel casting 1.4401 (AISI 316)
Max. ambient temperature	60 °C
Max. control range	4.0 bar
Max. input pressure	30 bar
Max. medium temperature	80 °C
Min. control range	0.4 bar
Page No.	HK151
Sealant	NBR
Size	4
Thread	G 1 1/2

Variants

Article number	Thread	Min. control range	Max. control range	Flow rate	Size	Price
137345	G 1 1/2	0.4 bar	4.0 bar	11330 l/min	4	2.035,48 € / Stk
137339	G 1/2	0.4 bar	4.0 bar	7850 l/min	3	514,68 € / Stk
137335	G 1/4	0.4 bar	4.0 bar	2095 l/min	1	475,03 € / Stk
137336	G 1/4	1.7 bar	17.5 bar	2095 l/min	1	475,03 € / Stk
137342	G 3/4	1.7 bar	17.5 bar	10055 l/min	3	514,68 € / Stk
137344	G 1	1.7 bar	17.5 bar	11330 l/min	4	2.035,48 € / Stk
137338	G 3/8	1.7 bar	17.5 bar	4420 l/min	1	475,03 € / Stk
137337	G 3/8	0.4 bar	4.0 bar	4420 l/min	1	475,03 € / Stk
137346	G 1 1/2	1.7 bar	17.5 bar	11330 l/min	4	2.035,48 € / Stk
137340	G 1/2	1.7 bar	17.5 bar	7850 l/min	3	514,68 € / Stk
137341	G 3/4	0.4 bar	4.0 bar	10055 l/min	3	514,68 € / Stk
137343	G 1	0.4 bar	4.0 bar	11330 l/min	4	2.035,48 € / Stk

More Pictures

