


Datasheet for: 100933


Filter regulator »Standard«, Protective cage, 40 μm , Size 4, G 1

Filter regulator »Standard«, PC container, Protective cage, 40 μm , Size 4, G 1, Input pressure max. 16 bar, 0.5 - 10 bar . Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Type number	678.43 S
Article number	100933
EAN/barcode	 4047322112192
Your price	289,47 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	125.0 mm
Bowl	Polycarbonate container with protective cage
C	190.6 mm
Condensate drain	Semi-automatic
D	261.4 mm
DN	25.0
F	145.0 mm
Filter rating	40.0 μm
Flow rate	7000 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK123
Pressure gauge display max.	16.0 bar

Pressure gauge
 display min. 0.0 bar
 Sealant NBR
 Series Standard
 Size 4
 Thread G 1

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	Price
100933	G 1	Aluminium, painted silver	40.0 μm	7000 l/min	4	289,47 € / Stk
100928	G 1/4	Die-cast zinc, painted silver	5.0 μm	900 l/min	1	71,29 € / Stk
100929	G 3/8	Die-cast zinc, painted silver	5.0 μm	900 l/min	1	70,59 € / Stk
100930	G 3/8	Die-cast zinc, painted silver	40.0 μm	1500 l/min	2	115,43 € / Stk
100931	G 1/2	Die-cast zinc, painted silver	5.0 μm	3000 l/min	3	114,31 € / Stk
100932	G 3/4	Aluminium, painted silver	40.0 μm	7000 l/min	4	289,47 € / Stk
174095	G 1	Aluminium, painted silver	40.0 μm	12000 l/min	4	289,47 € / Stk
174094	G 3/4	Aluminium, painted silver	40.0 μm	12000 l/min	4	289,47 € / Stk

More Pictures

