


Datasheet for: 103401


Ball valve fine adjustment, nickel-plated bright brass, G 3/4

Ball valve fine adjustment, Potable water suitable, nickel-plated bright brass, Temp. -15 °C to 100 °C, G 3/4, PN max 40 bar . Brass ball valves in the standard series with fine adjustment. Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line. The flow rate can be regulated extremely precisely as a result. The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

Type number	335.05
Article number	103401
EAN/barcode	 4047322205917
Your price	19,79 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	83.0 mm
B	76.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	20.0
DVGW approval	DIN EN 13828:2003-12, DVGW W 570
Housing	Nickel-plated brass (outside), brass with a bare metal surface (inside)
L	58.0 mm
Max. operating pressure	40 bar
Max. operating temperature	100 °C
Min. operating temperature	-15 °C
Page No.	WEB
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	NBR
Thread	G 3/4
Thread material	Brass with a bare metal surface
Wheel	Plastic

Variants

Article number	Thread	DN	Price
103401	G 3/4	20.0	19,79 € / Stk
103399	G 3/8	10.0	15,94 € / Stk
103400	G 1/2	15.0	16,97 € / Stk
103402	G 1	25.0	26,02 € / Stk
103403	G 1 1/4	32.0	37,98 € / Stk
103405	G 2	50.0	85,51 € / Stk

More Pictures

