

Datasheet for: 103407


Potable water ball valve, Manual lever, IT/IT, Rp 3/8

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20°C to 150°C, Rp 3/8, DN 10, PN max. 50 bar . Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Type number	3350.702
-------------	----------

Article number	103407
----------------	--------

EAN/barcode	 4047322401104
-------------	--

Your price	6,86 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	85.5 mm
Applications	Potable water, water
B	41.8 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	10.0
DVGW approval	DIN EN 13828:2003-12, DVGW W 570
E	11.4 mm
Hand lever	Steel with plastic coating
Housing	Chrome-plated brass
L	52.4 mm
Max. operating temperature	150 °C
Min. operating temperature	-20 °C
PN	50 bar
Page No.	WEB
Standard thread	Thread acc. to ISO 7-1
Stem seal	NBR / FKM
Thread	Rp 3/8
a/f	21 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103407	Rp 3/8	10.0	50 bar	21 mm	6,86 € / Stk
103410	Rp 1	25.0	40 bar	38 mm	19,27 € / Stk
103411	Rp 1 1/4	32.0	30 bar	47 mm	30,74 € / Stk
103412	Rp 1 1/2	40.0	30 bar	54 mm	43,53 € / Stk
103413	Rp 2	50.0	25 bar	66 mm	66,62 € / Stk
103406	Rp 1/4	8.0	50 bar	18 mm	6,65 € / Stk
103408	Rp 1/2	15.0	50 bar	25 mm	8,58 € / Stk
103409	Rp 3/4	20.0	40 bar	31 mm	13,48 € / Stk

More Pictures

